

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01  
Supersedes Version 4.00\*\*\*

Revision Date 15-Dec-2020  
Issuing date 15-Dec-2020

## SECTION 1: Identification of the substance / mixture and of the company / undertaking

### 1.1. Product identifier

Identification of the  
substance/preparation

# Neopentyl glycol flake

Chemical Name 2,2-Dimethylpropane-1,3-diol  
CAS-No 126-30-7  
EC No. 204-781-0  
Registration number (REACH) 01-2119480396-30

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Intermediate  
Formulation  
Distribution of substance  
laboratory chemicals  
Polymerization  
coatings  
Road and construction applications

Uses advised against None

### 1.3. Details of the supplier of the safety data sheet

Company/Undertaking Identification **OQ Chemicals GmbH**  
Rheinpromenade 4A  
D-40789 Monheim  
Germany

Product Information Product Stewardship  
FAX: +49 (0)208 693 2053  
email: sc.psq@oq.com

### 1.4. Emergency telephone number

Emergency telephone number +44 (0) 1235 239 670 (UK)  
available 24/7

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

This substance is classified based on Directive 1272/2008/EC and its amendments (CLP Regulation)

Serious eye damage/eye irritation Category 1, H318

#### Additional information

For full text of Hazard- and EU Hazard-statements see SECTION 16.

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## 2.2. Label elements

Labelling according to Regulation 1272/2008/EC and its amendments (CLP Regulation).

### Hazard pictograms



**Signal word**

**Danger**

**Hazard statements**

H318: Causes serious eye damage.

**Precautionary statements**

P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER/doctor.

## 2.3. Other hazards

Dust can form an explosive mixture in air

Components of the product may be absorbed into the body by inhalation and ingestion

**PBT and vPvB assessment**

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

## SECTION 3: Composition / information on ingredients

### 3.1. Substances

Component	CAS-No	REACH-No	1272/2008/EC	Concentration (%)
2,2-Dimethylpropane-1,3-diol	126-30-7	01-2119480396-30	Eye Dam. 1; H318	> 99,0

For full text of Hazard- and EU Hazard-statements see SECTION 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Keep at rest. Aerate with fresh air. When symptoms persist or in all cases of doubt seek medical advice.

#### Skin

Wash off immediately with plenty of water. When symptoms persist or in all cases of doubt seek medical advice.

#### Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## Ingestion

Call a physician immediately. Do not induce vomiting without medical advice.

## 4.2. Most important symptoms and effects, both acute and delayed

### Main symptoms

cough.

### Special hazard

Lung irritation.

## 4.3. Indication of any immediate medical attention and special treatment needed

### General advice

Remove contaminated, soaked clothing immediately and dispose of safely. First aider needs to protect himself.

Treat symptomatically. If ingested, irrigate the stomach using activated charcoal.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water spray

#### Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Under conditions giving incomplete combustion, hazardous gases produced may consist of:

carbon monoxide (CO)

carbon dioxide (CO<sub>2</sub>)

Combustion gases of organic materials must in principle be graded as inhalation poisons

Dust can form an explosive mixture in air

### 5.3. Advice for firefighters

#### Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

#### Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Keep people away from and upwind of fire.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: For personal protective equipment see section 8. Avoid contact with skin and eyes. Do not breathe dust. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.

For emergency responders: Personal protection see section 8.

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## 6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

## 6.3. Methods and material for containment and cleaning up

### Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

### Methods for cleaning up

Use mechanical handling equipment. Avoid dust formation. Keep in suitable, closed containers for disposal. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

## 6.4. Reference to other sections

For personal protective equipment see section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Further info may be available in the appropriate Exposure scenarios in the annex to this SDS.

#### Advice on safe handling

Avoid dust formation. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms.

#### Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

#### Advice on the protection of the environment

See Section 8: Environmental exposure controls.

#### Incompatible products

strong oxidizing agents

### 7.2. Conditions for safe storage, including any incompatibilities

#### Advice on protection against fire and explosion

Risk of dust explosion in fine crystalline powder form. Dust can form an explosive mixture in air. Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material.

#### Technical measures/Storage conditions

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care. Protect from moisture.

#### Temperature class

T2

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## 7.3. Specific end use(s)

Intermediate  
Formulation  
Distribution of substance  
laboratory chemicals  
Polymerization  
coatings  
Road and construction applications  
For specific end use information see the annex of this safety data sheet

## SECTION 8: Exposure controls / personal protection

### 8.1. Control parameters

#### Exposure limits European Union

No exposure limits established

#### Exposure limits UK

##### EH40 WELs

Component	TWA (mg/m <sup>3</sup> )	TWA (ppm)	STEL (mg/m <sup>3</sup> )	STEL (ppm)
Dust, general threshold limit value (inhalable fraction) CAS: -	10			
Dust, general threshold limit value (respirable fraction) CAS: -	4			

##### Note

For details and further information please refer to the original regulation.

#### DNEL & PNEC

##### 2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7

##### Workers

DN(M)EL - long-term exposure - systemic effects - Inhalation	35 mg/m <sup>3</sup>
DN(M)EL - acute / short-term exposure - systemic effects - Inhalation	Low hazard (no threshold derived)
DN(M)EL - long-term exposure - local effects - Inhalation	No hazard identified
DN(M)EL - acute / short-term exposure - local effects - Inhalation	No hazard identified
DN(M)EL - long-term exposure - systemic effects - Dermal	10 mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Dermal	No hazard identified
DN(M)EL - long-term exposure - local effects - Dermal	No hazard identified
DN(M)EL - acute / short-term exposure - local effects - Dermal	No hazard identified
DN(M)EL - local effects - eyes	Medium hazard (no threshold derived)

#### General population

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

DN(M)EL - long-term exposure - systemic effects - Inhalation	8,7 mg/m <sup>3</sup>
DN(M)EL - acute / short-term exposure - systemic effects - Inhalation	Low hazard (no threshold derived)
DN(M)EL - long-term exposure - local effects - Inhalation	No hazard identified
DN(M)EL - acute / short-term exposure - local effects - Inhalation	No hazard identified
DN(M)EL - long-term exposure - systemic effects - Dermal	5 mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Dermal	No hazard identified
DN(M)EL - long-term exposure - local effects - Dermal	No hazard identified
DN(M)EL - acute / short-term exposure - local effects - Dermal	No hazard identified
DN(M)EL - long-term exposure - systemic effects - Oral	5 mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Oral	Low hazard (no threshold derived)
DN(M)EL - local effects - eyes	Medium hazard (no threshold derived)

## Environment

PNEC aqua - freshwater	5 mg/l
PNEC aqua - marine water	0,5 mg/l
PNEC aqua - intermittent releases	5 mg/l
PNEC STP	20 mg/l
PNEC sediment - freshwater	18,5 mg/kg dw***
PNEC sediment - marine water	1,85 mg/kg dw***
PNEC Air	No hazard identified
PNEC soil	0,77*** mg/kg dw***
Secondary poisoning	No potential for bioaccumulation

## 8.2. Exposure controls

### Special adaptations (REACH)

Not applicable.

### Appropriate Engineering controls

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

### Personal protective equipment

#### General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe dust or mist. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

#### Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Equipment should conform to EN 166

#### Hand protection

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

<b>Suitable material</b>	nitrile rubber
<b>Evaluation</b>	according to EN 374: level 6
<b>Glove thickness</b>	approx 0,55 mm
<b>Break through time</b>	> 480 min
<b>Suitable material</b>	polyvinylchloride
<b>Evaluation</b>	Information derived from practical experience
<b>Glove thickness</b>	approx 0,8 mm

## Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

## Respiratory protection

Respirator with P3 filter. Full mask with above mentioned filter according to producers using requirements or self-contained breathing apparatus. Equipment should conform to EN 136 or EN 140 and EN 143.

## Environmental exposure controls

If possible use in closed systems. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. Observe the exposure limits, clean exhaust air if needed. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

## Additional advice

Further details on substance data can be found in the registration dossier under the following link:  
<http://echa.europa.eu/information-on-chemicals/registered-substances>. For specific exposure controls see the annex to this safety data sheet.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	crystalline Flakes
<b>Granulometry</b>	
Fraction µm	
< 200	97
< 125	57
< 71	16
< 51	9
Median	M = 120 µm
<b>Colour</b>	white
<b>Odour</b>	sweet
<b>Odour threshold</b>	No data available
<b>pH</b>	not applicable
<b>Melting point/range</b>	128 °C
<b>Method</b>	DIN 53171***
<b>Boiling point/range</b>	208,5 °C @ 1013 hPa
<b>Method</b>	DIN 53171***
<b>Flash point</b>	107 °C
<b>Method</b>	closed cup
<b>Evaporation rate</b>	No data available

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

**Flammability (solid, gas)** No data available  
**Lower explosion limit** 1,1 Vol %  
**Upper explosion limit** 11,4 Vol %

## Vapour pressure

Values [hPa]	Values [kPa]	Values [atm]	@ °C	@ °F	Method
0,03***	0,003***	< 0,001	20	68	OECD 104***
6,9	0,69	0,007	90	194	OECD 104***
88	8,8	0,087	140	284	OECD 104***

**Vapour density** No data available

## Relative density

Values	@ °C	@ °F	Method
1,035	20	68	OECD 109

**Solubility** 830 g/l @ 20 °C, in water

**log Pow** 0 @ 25 °C (77 °F), OECD 117\*\*\*

**Autoignition temperature** 375 °C

**Decomposition temperature** No data available

**Viscosity** 6,43 mPa\*s @ 139 °C

**Method** dynamic

**Explosive properties** Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties

**Oxidizing properties** Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties

## 9.2. Other information

**Molecular weight** 104,15

**Molecular formula** C5 H12 O2

**Minimum ignition energy** 150 mJ < E min. < 260 mJ with inductivity

**log Koc** 0,019 @ 25°C (77 °F) calculated\*\*\*

**Bulk density** ~ 500 kg/m<sup>3</sup> @ 20 °C (68 °F)

**Surface tension** 72 mN/m (1 g/l @ 20°C (68°F)), OECD 115

hygroscopic. Dust can form an explosive mixture in air.

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

Dust can form an explosive mixture in air.

### 10.4. Conditions to avoid



# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.

## 10.5. Incompatible materials

strong oxidizing agents.

## 10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure Ingestion, Skin contact, Inhalation, Eye contact

Acute toxicity				
2,2-Dimethylpropane-1,3-diol (126-30-7)				
Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	> 6400 mg/kg	rat, male/female	OECD 401
Oral	LD50	6920 mg/kg	rat, male/female	OECD 401
Inhalative	LC0	140 mg/m <sup>3</sup> (8 h) <sup>***</sup>	rat, male/female	OECD 403
Dermal	LD50	> 4000 mg/kg	guinea pig	OECD 402

#### 2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7

##### Assessment

Based on available data, the classification criteria are not met for:

Acute oral toxicity

Acute dermal toxicity

Acute inhalation toxicity

Irritation and corrosion				
2,2-Dimethylpropane-1,3-diol (126-30-7)				
Target Organ Effects	Species	Result	Method	
Skin	rabbit	Mild skin irritation	OECD 404	4h
Eyes	rabbit	severe irritation	OECD 405	

#### 2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7

##### Assessment

The available data lead to the classification given in section 2

Based on available data, the classification criteria are not met for:

skin irritation/corrosion

Sensitization				
2,2-Dimethylpropane-1,3-diol (126-30-7)				
Target Organ Effects	Species	Evaluation	Method	
Skin	mouse	not sensitizing	OECD 429	

#### 2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7

##### Assessment

Based on available data, the classification criteria are not met for:

Skin sensitization

For respiratory sensitization, no data are available

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

<b>Subacute, subchronic and prolonged toxicity</b>				
<b>2,2-Dimethylpropane-1,3-diol (126-30-7)</b>				
Type	Dose	Species	Method	
Subchronic toxicity	NOAEL: 1000 mg/kg/d***	rat, male/female	OECD 408	Oral
Subacute toxicity	NOAEL: 300 mg/kg/d***	rat, male***	OECD 422***	Inhalation Oral***

## **2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7**

### **Assessment**

Based on available data, the classification criteria are not met for:  
STOT RE

<b>Carcinogenicity, Mutagenicity, Reproductive toxicity</b>					
<b>2,2-Dimethylpropane-1,3-diol (126-30-7)</b>					
Type	Dose	Species	Evaluation	Method	
Mutagenicity		Salmonella typhimurium	negative	OECD 471 (Ames)	In vitro study
Mutagenicity		CHO (Chinese Hamster Ovary) cells***	negative	OECD 476 (Mammalian Gene Mutation)	In vitro study
Mutagenicity		CHL	negative	Chromosomal Aberration	In vitro study
Reproductive toxicity***	NOAEL 1000 mg/kg/d	rat***		OECD 422, Oral	Reproduction / developmental Toxicity***
Developmental Toxicity***	NOAEL 1000 mg/kg/d	rat***		OECD 414	Maternal toxicity Developmental toxicity***

## **2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7**

### **CMR Classification**

The available data on CMR properties are summarized in the table above. They do not indicate a classification into categories 1A or 1B

### **Evaluation**

Did not show reprotoxic or mutagenic effects in animal experiments  
In the absence of specific alerts no cancer testing is required

## **2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7**

### **Main symptoms**

cough.

### **Target Organ Systemic Toxicant - Single exposure**

Based on available data, the classification criteria are not met for:  
STOT SE

### **Target Organ Systemic Toxicant - Repeated exposure**

Based on available data, the classification criteria are not met for:  
STOT RE

### **Other adverse effects**

Components of the product may be absorbed into the body by inhalation and ingestion.

### **Note**

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link:

<http://echa.europa.eu/information-on-chemicals/registered-substances>.

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## SECTION 12: Ecological information

### 12.1. Toxicity

Acute aquatic toxicity			
2,2-Dimethylpropane-1,3-diol (126-30-7)			
Species	Exposure time	Dose	Method
Daphnia magna (Water flea)	48h	EC50: > 500 mg/l	84/449/EEC C.2
Desmodesmus subspicatus	72h	EC20: > 500 mg/l	DIN 38412, part 9
Oryzias latipes (Medaka)	48h	LC50: > 10000 mg/l	JIS
Leuciscus idus (Golden orfe)	48h	LC0: 10000 mg/l	
Activated sludge (domestic)	24h	TTC: 2000 mg/l	ETAD Fermentation tube method

Long term toxicity				
2,2-Dimethylpropane-1,3-diol (126-30-7)				
Type	Species	Dose	Method	
Mortality	Daphnia magna (Water flea)	NOEC: > 1000 mg/l (21 d)		

### 12.2. Persistence and degradability

**2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7**

#### Biodegradation

80-90 % (28\*\*\* d), activated sludge, domestic, aerobic, non-adapted, Readily biodegradable, OECD 301 B.

Abiotic Degradation			
2,2-Dimethylpropane-1,3-diol (126-30-7)			
Type	Result	Method	
Hydrolysis	Half-life (DT50): t1/2 (pH 4 ): 1 yr @ 25°C	OECD 111	
Hydrolysis	Half-life (DT50): t1/2 (pH 7 ): 1 yr @ 25°C	OECD 111	
Hydrolysis	Half-life (DT50): t1/2 (pH 9 ): 1 yr @ 25°C	OECD 111	
Photolysis	Photochemical reaction with OH Radicals Half-life (DT50): 1,851 d @ 25°C	SRC AOP v1.92	

### 12.3. Bioaccumulative potential

2,2-Dimethylpropane-1,3-diol (126-30-7)		
Type	Result	Method
log Pow	0 @ 25 °C (77 °F)***	OECD 107***
BCF	< 9	OECD 305 C

### 12.4. Mobility in soil

2,2-Dimethylpropane-1,3-diol (126-30-7)		
---	--	--

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

Type	Result	Method
Distribution to environmental compartments	Air: 0,001 Soil: 0,0627 % Water: 99,9 % Sediment: 0,001%, Suspended sediment: < 0,001% Biota: < 0,001%***	Calculation according Mackay, Level I
Adsorption/Desorption	log koc: 0,019 @ 25 °C ( 77 °F)***	calculated***
Surface tension	72 mN/m (1 g/l @ 20°C (68°F))	OECD 115

## 12.5. Results of PBT and vPvB assessment

### 2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7

#### **PBT and vPvB assessment**

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

## 12.6. Other adverse effects

### 2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **Product Information**

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Hazardous waste according to European Waste Catalogue (EWC)

#### **Uncleaned empty packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

## SECTION 14: Transport information

### Section 14.1 - 14.6

#### ADR/RID

Not restricted

#### ADN

ADN Container  
Not restricted

#### ICAO-TI / IATA-DGR

Not restricted

#### IMDG

Not restricted

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code** not applicable

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

### Regulation 1272/2008, Annex VI

not listed

### DI 2012/18/EU (Seveso III)

**Category** not subject

### DI 1999/13/EC (VOC Guideline)

Component	Status
2,2-Dimethylpropane-1,3-diol CAS: 126-30-7	not subject

### International Inventories

#### **2,2-Dimethylpropane-1,3-diol, CAS: 126-30-7**

AICS (AU)  
DSL (CA)  
IECSC (CN)  
EC-No. 2047810 (EU)  
ENCS (2)-240 (JP)  
ISHL (2)-240 (JP)  
KECI KE-11811 (KR)  
INSQ (MX)  
PICCS (PH)  
TSCA (US)  
NZIoC (NZ)  
TCSI (TW)

### National regulatory information Great Britain

#### **Releases to air (Pollution Inventory Substances)**

Component	Annual reporting level threshold
2,2-Dimethylpropane-1,3-diol CAS: 126-30-7	not listed
Dust, general threshold limit value (inhalable fraction) CAS: -	10 tonnes, listed as particulates - total

#### **Releases to water (Pollution Inventory Substances)**

Component	Annual reporting level threshold
2,2-Dimethylpropane-1,3-diol	not listed

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

CAS: 126-30-7	
---------------	--

## Releases to sewer (Pollution Inventory Substances)

Component	Annual reporting level threshold
2,2-Dimethylpropane-1,3-diol CAS: 126-30-7	not listed

For details and further information please refer to the original regulation

## 15.2. Chemical safety assessment

The Chemical Safety Report (CSR) has been generated. For Exposure Scenarios see the annex.

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3

H318: Causes serious eye damage.

### Abbreviations

A table of terms and abbreviations can be found under the following link:

[http://echa.europa.eu/documents/10162/13632/information\\_requirements\\_r20\\_en.pdf](http://echa.europa.eu/documents/10162/13632/information_requirements_r20_en.pdf)

### Training advice

For effective first-aid, special training / education is needed.

### Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on OQ owned data and public sources deemed valid or acceptable. The absence of data elements required by OSHA, ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

### Further information for the safety data sheet

Changes against the previous version are marked by \*\*\*. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the OQ homepage ([www.chemicals.oq.com](http://www.chemicals.oq.com)).

### Disclaimer

**For industrial use only.** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. OQ makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

End of Safety Data Sheet

# Annex to the extended Safety Data Sheet (eSDS)

## General information

Environmental compartment

In the absence of environmental hazards no environmental risk assessment was carried out

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

A quantitative approach used to conclude safe use for:  
Long-term Systemic effects via inhalation  
Long-term Systemic effects via skin\*\*\*

## **Operational conditions and risk management measures**

Wear suitable gloves tested to EN 374 for activities, where direct contact with substance is possible  
Wear suitable eye protection, where direct contact (e.g. splashes) with substance is possible

## Exposure scenario identification

- 1 **Industrial use resulting in manufacture of another substance (use of intermediates)**
- 2 **Formulation & (re)packing of substances and mixtures**
- 3 **Distribution of substance**
- 4 **Use in laboratories**
- 5 **Use in laboratories**
- 6 **Polymerisation**
- 7 **Uses in coatings**
- 8 **Uses in coatings**
- 9 **Road and construction applications**
- 10 **Road and construction applications**

## **Number of the ES 1**

Short title of the exposure scenario

**Industrial use resulting in manufacture of another substance (use of intermediates)**

## **List of use descriptors**

### **Sector of uses [SU]**

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites  
SU8: Manufacture of bulk, large scale chemicals (including petroleum products)  
SU9: Manufacture of fine chemicals

### **Process categories [PROC]**

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC15: Use as laboratory reagent

### **Environmental release categories [ERC]**

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

### **Product characteristics**

Refer to attached safety data sheets

### **Processes and activities covered by the exposure scenario**

Use as an intermediate (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine)

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

vessel/barge, road/rail car and bulk container).

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

**Number of the contributing scenario** 1  
**Contributing exposure scenario controlling worker exposure for PROC 1**

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 2**

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 3**

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).



# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

**Number of the contributing scenario** 4  
**Contributing exposure scenario controlling worker exposure for PROC 4**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 5  
**Contributing exposure scenario controlling worker exposure for PROC 5**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

4 h (half shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 6  
**Contributing exposure scenario controlling worker exposure for PROC 8a**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

4 h (half shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 7  
**Contributing exposure scenario controlling worker exposure for PROC 8b**

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 9

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 15

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Exposure estimation and reference to its source

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.01 ; EE(derm): 0.34
Proc 2	EE(inhal): 0.01 ; EE(derm): 1.37
Proc 3	EE(inhal): 0.10 ; EE(derm): 0.69
Proc 4	EE(inhal): 0.50 ; EE(derm): 6.86
Proc 5	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8a	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8b	EE(inhal): 0.06 ; EE(derm): 8.226
Proc 9	EE(inhal): 0.10 ; EE(derm): 6.86
Proc 15	EE(inhal): 0.50 ; EE(derm): 0.34

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.001 ; RCR(derm): 0.01
Proc 2	RCR(inhal): 0.01 ; RCR(derm): 0.137
Proc 3	RCR(inhal): 0.01 ; RCR(derm): 0.069
Proc 4	RCR(inhal): 0.014 ; RCR(derm): 0.686
Proc 5	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8a	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8b	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 9	RCR(inhal): 0.01 ; RCR(derm): 0.686
Proc 15	RCR(inhal): 0.010 ; RCR(derm): 0.070

## Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as  $M(\text{site})$  [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

### associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

## Number of the ES 2

Short title of the exposure scenario

## Formulation & (re)packing of substances and mixtures

### Sector of uses [SU]

SU10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC15: Use as laboratory reagent

## **Environmental release categories [ERC]**

ERC2: Formulation of preparations (mixtures)  
ERC3: Formulation in materials

## **Product characteristics**

Refer to attached safety data sheets

## **Processes and activities covered by the exposure scenario**

Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

## **Further explanations**

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

## **Number of the contributing scenario**

1

### **Contributing exposure scenario controlling worker exposure for PROC 1**

#### **Further specification**

Assessment tool used: Chesar 2.2

#### **Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

#### **Frequency and duration of use**

8 h (full shift)

#### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

#### **Other given operational conditions affecting workers exposure**

Indoor and outdoor use

#### **Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## **Number of the contributing scenario**

2

### **Contributing exposure scenario controlling worker exposure for PROC 2**

#### **Further specification**

Assessment tool used: Chesar 2.2

#### **Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

#### **Frequency and duration of use**

8 h (full shift)

#### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

#### **Other given operational conditions affecting workers exposure**

Indoor and outdoor use

#### **Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## **Number of the contributing scenario**

3

### **Contributing exposure scenario controlling worker exposure for PROC 3**

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 5

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 8b

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

4 h (half shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario**

**7**

**Contributing exposure scenario controlling worker exposure for PROC 9**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario**

**8**

**Contributing exposure scenario controlling worker exposure for PROC 15**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Human exposure prediction (oral, dermal, inhalative)**

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.01 ; EE(derm): 0.34
Proc 2	EE(inhal): 0.01 ; EE(derm): 1.37
Proc 3	EE(inhal): 0.10 ; EE(derm): 0.69
Proc 5	EE(inhal): 0.3 ; EE(derm): 8.226

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

Proc 8a	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8b	EE(inhal): 0.06 ; EE(derm): 8.226
Proc 9	EE(inhal): 0.10 ; EE(derm): 6.86
Proc 15	EE(inhal): 0.10 ; EE(derm): 0.34

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.01 ; RCR(derm): 0.01
Proc 2	RCR(inhal): 0.01 ; RCR(derm): 0.137
Proc 3	RCR(inhal): 0.01 ; RCR(derm): 0.069
Proc 5	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8a	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8b	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 9	RCR(inhal): 0.010 ; RCR(derm): 0.686
Proc 15	RCR(inhal): 0.010 ; RCR(derm): 0.034

## Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as  $M(\text{site})$  [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

### associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

## Number of the ES 3

Short title of the exposure scenario

### Distribution of substance

### Sector of uses [SU]

SU8: Manufacture of bulk, large scale chemicals (including petroleum products)

SU9: Manufacture of fine chemicals

SU10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

### Environmental release categories [ERC]

ERC2: Formulation of preparations (mixtures)

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

## Contributing Scenarios

<b>Number of the contributing scenario</b>	<b>1</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 1</b>	

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

<b>Number of the contributing scenario</b>	<b>2</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 2</b>	

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

<b>Number of the contributing scenario</b>	<b>3</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 3</b>	

### Further specification

Assessment tool used: Chesar 2.2



# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 5

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 8b

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.01 ; EE(derm): 0.34
Proc 2	EE(inhal): 0.01 ; EE(derm): 1.37
Proc 3	EE(inhal): 0.10 ; EE(derm): 0.69
Proc 5	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8a	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8b	EE(inhal): 0.06 ; EE(derm): 8.226
Proc 9	EE(inhal): 0.10 ; EE(derm): 6.86
Proc 15	EE(inhal): 0.10 ; EE(derm): 0.34

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.01 ; RCR(derm): 0.01
Proc 2	RCR(inhal): 0.01 ; RCR(derm): 0.137
Proc 3	RCR(inhal): 0.01 ; RCR(derm): 0.069
Proc 5	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8a	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8b	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 9	RCR(inhal): 0.01 ; RCR(derm): 0.686
Proc 15	RCR(inhal): 0.01 ; RCR(derm): 0.034

## Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as M(site) [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

### associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

## Number of the ES 4

Short title of the exposure scenario

### Use in laboratories

### List of use descriptors

### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

### Process categories [PROC]

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

### Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

### Product characteristics

Refer to attached safety data sheets

### Processes and activities covered by the exposure scenario

Use of the substance within laboratory settings, including material transfers and equipment cleaning

### Further explanations

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

Industrial use  
Assumes use at not more than 20°C above ambient temperature (unless stated differently)

**Number of the contributing scenario** 1  
**Contributing exposure scenario controlling worker exposure for PROC 8a**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

4 h (half shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 8b**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

4 h (half shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 9**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 4

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 8a	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8b	EE(inhal): 0.06 ; EE(derm): 8.226
Proc 9	EE(inhal): 0.10 ; EE(derm): 6.86
Proc 15	EE(inhal): 0.10 ; EE(derm): 0.34

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 8a	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8b	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 9	RCR(inhal): 0.01 ; RCR(derm): 0.686
Proc 15	RCR(inhal): 0.01 ; RCR(derm): 0.034

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as M(site) [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

### associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

Number of the ES 5

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

Short title of the exposure scenario

## Use in laboratories

### Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU24: Scientific research and development

### Process categories [PROC]

PROC15: Use as laboratory reagent

### Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

### Product characteristics

Refer to attached safety data sheets

### Processes and activities covered by the exposure scenario

Use of small quantities within laboratory settings, including material transfers and equipment cleaning

### Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

### Number of the contributing scenario

1

### Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm):

Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 15

EE(inhal): 0.01 ; EE(derm): 0.34

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

Proc 15

RCR(inhal): 0.01 ; RCR(derm): 0.034

## Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as  $M(\text{site})$  [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

### associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

## Number of the ES 6

Short title of the exposure scenario

### Polymerisation

### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

SU12: Manufacture of plastics products, including compounding and conversion

### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

### Environmental release categories [ERC]

ERC6c: Industrial use of monomers for manufacture of thermoplastics

### Product characteristics

Refer to attached safety data sheets

### Processes and activities covered by the exposure scenario

Processing of formulated polymers including material transfers, moulding and forming activities, material re-works and associated maintenance

### Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

### Number of the contributing scenario

1

### Contributing exposure scenario controlling worker exposure for PROC 1

### Further specification

Assessment tool used: Chesar 2.2

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

2

## Contributing exposure scenario controlling worker exposure for PROC 2

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

3

## Contributing exposure scenario controlling worker exposure for PROC 3

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)



# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 5  
**Contributing exposure scenario controlling worker exposure for PROC 5**

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 6  
**Contributing exposure scenario controlling worker exposure for PROC 8a**

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 7  
**Contributing exposure scenario controlling worker exposure for PROC 8b**

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 8  
**Contributing exposure scenario controlling worker exposure for PROC 9**

#### Further specification

Assessment tool used: Chesar 2.2

#### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

#### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 9  
**Contributing exposure scenario controlling worker exposure for PROC 15**

#### Further specification

Assessment tool used: Chesar 2.2

#### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Solid, low dustiness

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

#### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

#### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.01 ; EE(derm): 0.034
Proc 2	EE(inhal): 0.01 ; EE(derm): 1.37
Proc 3	EE(inhal): 0.1 ; EE(derm): 0.69
Proc 4	EE(inhal): 0.5 ; EE(derm): 6.86
Proc 5	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8a	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8b	EE(inhal): 0.06 ; EE(derm): 8.226
Proc 9	EE(inhal): 0.1 ; EE(derm): 6.86
Proc 15	EE(inhal): 0.1 ; EE(derm): 0.34

#### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio;

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.01 ; RCR(derm): 0.01
Proc 2	RCR(inhal): 0.01 ; RCR(derm): 0.137
Proc 3	RCR(inhal): 0.01 ; RCR(derm): 0.069
Proc 4	RCR(inhal): 0.014 ; RCR(derm): 0.686
Proc 5	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8a	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8b	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 9	RCR(inhal): 0.01 ; RCR(derm): 0.686
Proc 15	RCR(inhal): 0.010 ; RCR(derm): 0.034

## **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as M(site) [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

### **associated uses:**

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

## **Number of the ES 7**

Short title of the exposure scenario

### **Uses in coatings**

#### **List of use descriptors**

#### **Sector of uses [SU]**

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

SU5: Manufacture of textiles, leather, fur

SU6a: Manufacture of wood and wood products

SU6b: Manufacture of pulp, paper and paper products

SU7: Printing and reproduction of recorded media

SU8: Manufacture of bulk, large scale chemicals (including petroleum products)

SU10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU11: Manufacture of rubber products

SU12: Manufacture of plastics products, including compounding and conversion

SU13: Manufacture of other non-metallic mineral products, e.g. plasters, cement

#### **Process categories [PROC]**

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC6: Calendaring operations

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC10: Roller application or brushing  
PROC13: Treatment of articles by dipping and pouring  
PROC14: production of preparations or articles by tableting, compression, extrusion, pelettisation  
PROC15: Use as laboratory reagent

## **Environmental release categories [ERC]**

ERC5: Industrial use resulting in inclusion into or onto a matrix

## **Product characteristics**

Refer to attached safety data sheets

## **Processes and activities covered by the exposure scenario**

Processing of formulated polymers including material transfers, additives handling (e.g. pigments, stabilisers, fillers, plasticisers, etc.), moulding, curing and forming activities, material re-works, storage and associated maintenance.

## **Further explanations**

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

<b>Number of the contributing scenario</b>	<b>1</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 1</b>	

### **Further specification**

Assessment tool used: Chesar 2.2

### **Product characteristics**

Covers percentage substance in the product up to 25 %

### **Frequency and duration of use**

8 h (full shift)

### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### **Other given operational conditions affecting workers exposure**

Indoor and outdoor use

### **Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

<b>Number of the contributing scenario</b>	<b>2</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 2</b>	

### **Further specification**

Assessment tool used: Chesar 2.2

### **Product characteristics**

Covers percentage substance in the product up to 25 %

### **Frequency and duration of use**

8 h (full shift)

### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### **Other given operational conditions affecting workers exposure**

Indoor and outdoor use

### **Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

<b>Number of the contributing scenario</b>	<b>3</b>
<b>Contributing exposure scenario controlling worker exposure for</b>	

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## PROC 3

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Number of the contributing scenario

4

### Contributing exposure scenario controlling worker exposure for PROC 4

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Number of the contributing scenario

5

### Contributing exposure scenario controlling worker exposure for PROC 5

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

### Number of the contributing scenario

6

### Contributing exposure scenario controlling worker exposure for PROC 6

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation, provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374.

**Number of the contributing scenario**

7

**Contributing exposure scenario controlling worker exposure for PROC 7**

**Further specification**

Assessment tool used: StoffenManager RiskOfDerm

**Product characteristics**

Covers percentage substance in the product up to 25 %

**Frequency and duration of use**

4 h (half shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to hands and lower arms (1500 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor use

**Number of the contributing scenario**

8

**Contributing exposure scenario controlling worker exposure for PROC 8a**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 25 %

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

**Number of the contributing scenario**

9

**Contributing exposure scenario controlling worker exposure for PROC 8b**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 25 %

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80% %).

**Number of the contributing scenario** 10  
**Contributing exposure scenario controlling worker exposure for PROC 9**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 25 %

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 11  
**Contributing exposure scenario controlling worker exposure for PROC 10**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 25 %

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

**Number of the contributing scenario** 12  
**Contributing exposure scenario controlling worker exposure for PROC 13**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 25 %

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

**Number of the contributing scenario** 13  
**Contributing exposure scenario controlling worker exposure for PROC 14**

#### Further specification

Assessment tool used: Chesar 2.2

#### Product characteristics

Covers percentage substance in the product up to 25 %

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

#### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 14  
**Contributing exposure scenario controlling worker exposure for PROC 15**

#### Further specification

Assessment tool used: Chesar 2.2

#### Product characteristics

Covers percentage substance in the product up to 25 %

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

#### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

#### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.026 ; EE(derm): 0.02
Proc 2	EE(inhal): 2.6 ; EE(derm): 0.822
Proc 3	EE(inhal): 7.8 ; EE(derm): 0.414
Proc 4	EE(inhal): 13 ; EE(derm): 4.116
Proc 5	EE(inhal): 13 ; EE(derm): 1.645
Proc 6	EE(inhal): 13 ; EE(derm): 3.292
Proc 7	EE(inhal): 0.00 ; EE(derm): 0.61
Proc 8a	EE(inhal): 18.2 ; EE(derm): 1.645
Proc 8b	EE(inhal): 13 ; EE(derm): 1.645
Proc 9	EE(inhal): 13 ; EE(derm): 4.116
Proc 10	EE(inhal): 18.2 ; EE(derm): 3.292
Proc 13	EE(inhal): 18.2 ; EE(derm): 1.645
Proc 14	EE(inhal): 13 ; EE(derm): 2.058
Proc 15	EE(inhal): 13 ; EE(derm): 0.204

#### Risk characterisation



# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.01 ; RCR(derm): 0.01
Proc 2	RCR(inhal): 0.074 ; RCR(derm): 0.082
Proc 3	RCR(inhal): 0.223 ; RCR(derm): 0.041
Proc 4	RCR(inhal): 0.371 ; RCR(derm): 0.412
Proc 5	RCR(inhal): 0.371 ; RCR(derm): 0.164
Proc 6	RCR(inhal): 0.371 ; RCR(derm): 0.329
Proc 7	RCR(inhal): 0.000 ; RCR(derm): 0.061
Proc 8a	RCR(inhal): 0.52 ; RCR(derm): 0.164
Proc 8b	RCR(inhal): 0.371 ; RCR(derm): 0.164
Proc 9	RCR(inhal): 0.371 ; RCR(derm): 0.412
Proc 10	RCR(inhal): 0.52 ; RCR(derm): 0.329
Proc 13	RCR(inhal): 0.52 ; RCR(derm): 0.164
Proc 14	RCR(inhal): 0.371 ; RCR(derm): 0.206
Proc 15	RCR(inhal): 0.371 ; RCR(derm): 0.02

## **Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as M(site) [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

### **associated uses:**

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

## **Number of the ES 8**

Short title of the exposure scenario

### **Uses in coatings**

#### **Sector of uses [SU]**

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### **Process categories [PROC]**

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC6: Calendering operations

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

PROC14: production of preparations or articles by tableting, compression, extrusion, pelettisation

#### **Environmental release categories [ERC]**

ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix

ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

ERC10a: Wide dispersive outdoor use of long-life articles and materials with low release

ERC10b: Wide dispersive outdoor use of long-life articles and materials with high or intended release (including abrasive processing)

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

ERC11a: Wide dispersive indoor use of long-life articles and materials with low release

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Processing of formulated polymers including material transfers, additives handling (e.g. pigments, stabilisers, fillers, plasticisers, etc.), moulding, curing and forming activities, material re-works, storage and associated maintenance.

## Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

<b>Number of the contributing scenario</b>	<b>1</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 5</b>	

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation, provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

<b>Number of the contributing scenario</b>	<b>2</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 6</b>	

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

4 h (half shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation, provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

<b>Number of the contributing scenario</b>	<b>3</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 8a</b>	

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

## Frequency and duration of use

4 h (half shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation, provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation, provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 10

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

4 h (half shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation, provide a good standard of controlled ventilation (5 to 10 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

8 h (full shift)

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 14

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 5	EE(inhal): 26 ; EE(derm): 1.645
Proc 6	EE(inhal): 15.6 ; EE(derm): 3.292
Proc 8a	EE(inhal): 27.3 ; EE(derm): 1.645
Proc 8b	EE(inhal): 26 ; EE(derm): 1.645
Proc 10	EE(inhal): 11.7 ; EE(derm): 3.292
Proc 13	EE(inhal): 18.2 ; EE(derm): 1.645
Proc 14	EE(inhal): 26 ; EE(derm): 2.058

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 5	RCR(inhal): 0.743 ; RCR(derm): 0.164
Proc 6	RCR(inhal): 0.446 ; RCR(derm): 0.329
Proc 8a	RCR(inhal): 0.78 ; RCR(derm): 0.164
Proc 8b	RCR(inhal): 0.743 ; RCR(derm): 0.164
Proc 10	RCR(inhal): 0.334 ; RCR(derm): 0.329
Proc 13	RCR(inhal): 0.52 ; RCR(derm): 0.164
Proc 14	RCR(inhal): 0.743 ; RCR(derm): 0.206

## Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as  $M(\text{site})$  [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

## associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

## Number of the ES 9

Short title of the exposure scenario

### Road and construction applications

#### Sector of uses [SU]

SU13: Manufacture of other non-metallic mineral products, e.g. plasters, cement

SU19: Building and construction work

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC13: Treatment of articles by dipping and pouring

PROC14: production of preparations or articles by tableting, compression, extrusion, pelettisation

PROC15: Use as laboratory reagent

#### Environmental release categories [ERC]

ERC2: Formulation of preparations (mixtures)

ERC3: Formulation in materials

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

ERC5: Industrial use resulting in inclusion into or onto a matrix

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Application of surface coatings and binders in road and construction activities, including paving uses, manual mastic and in the application of roofing and water-proofing membranes

#### Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

#### Number of the contributing scenario

1

#### Contributing exposure scenario controlling worker exposure for PROC 1

#### Further specification

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %  
Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 2

**Contributing exposure scenario controlling worker exposure for PROC 2**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 3

**Contributing exposure scenario controlling worker exposure for PROC 3**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 4

**Contributing exposure scenario controlling worker exposure for PROC 4**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 5  
**Contributing exposure scenario controlling worker exposure for PROC 5**

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 10 %

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 6  
**Contributing exposure scenario controlling worker exposure for PROC 8a**

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 10 %

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 7  
**Contributing exposure scenario controlling worker exposure for PROC 8b**

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 10 %

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 8  
**Contributing exposure scenario controlling worker exposure for PROC 9**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 9  
**Contributing exposure scenario controlling worker exposure for PROC 13**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 10  
**Contributing exposure scenario controlling worker exposure for PROC 14**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 11  
**Contributing exposure scenario controlling worker exposure for PROC 15**



# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

## Further specification

Assessment tool used: Chesar 2.2

## Product characteristics

Covers percentage substance in the product up to 10 %

Solid, low dustiness

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.006 ; EE(derm): 0.02
Proc 2	EE(inhal): 0.006 ; EE(derm): 0.822
Proc 3	EE(inhal): 0.06 ; EE(derm): 0.414
Proc 4	EE(inhal): 0.3 ; EE(derm): 4.116
Proc 5	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8a	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8b	EE(inhal): 0.06 ; EE(derm): 8.226
Proc 9	EE(inhal): 0.06 ; EE(derm): 4.116
Proc 13	EE(inhal): 0.06 ; EE(derm): 8.226
Proc 14	EE(inhal): 0.06 ; EE(derm): 2.058
Proc 15	EE(inhal): 0.06 ; EE(derm): 0.204

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.01 ; RCR(derm): 0.01
Proc 2	RCR(inhal): 0.01 ; RCR(derm): 0.082
Proc 3	RCR(inhal): 0.01 ; RCR(derm): 0.041
Proc 4	RCR(inhal): 0.01 ; RCR(derm): 0.412
Proc 5	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8a	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8b	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 9	RCR(inhal): 0.01 ; RCR(derm): 0.412
Proc 13	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 14	RCR(inhal): 0.01 ; RCR(derm): 0.206
Proc 15	RCR(inhal): 0.01 ; RCR(derm): 0.02

## Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as M(site) [see amounts used, contributing scenario 1] x release factor [Technical conditions and

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

measures at process level (source) to prevent release; contributing scenario 1])

## associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe

## Number of the ES 10

Short title of the exposure scenario

### Road and construction applications

#### Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process categories [PROC]

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC14: production of preparations or articles by tableting, compression, extrusion, pelettisation

PROC19: Hand-mixing with intimate contact and only PPE available

#### Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

ERC8c: Wide dispersive indoor use resulting in inclusion into or onto a matrix

ERC8d: Wide dispersive outdoor use of processing aids in open systems

ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Application of surface coatings and binders in road and construction activities, including paving uses, manual mastic and in the application of roofing and water-proofing membranes

#### Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

#### Number of the contributing scenario

1

#### Contributing exposure scenario controlling worker exposure for PROC 5

#### Further specification

Assessment tool used: Chesar 2.2

#### Product characteristics

Covers percentage substance in the product up to 10 %

Solid, low dustiness

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 8a**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 8b**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 4  
**Contributing exposure scenario controlling worker exposure for PROC 10**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

**Number of the contributing scenario** 5  
**Contributing exposure scenario controlling worker exposure for PROC 11**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

4 h (half shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to hands and lower arms (1500 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

**Number of the contributing scenario** 6  
**Contributing exposure scenario controlling worker exposure for PROC 13**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 7  
**Contributing exposure scenario controlling worker exposure for PROC 14**

**Further specification**

Assessment tool used: Chesar 2.2

**Product characteristics**

Covers percentage substance in the product up to 10 %

Solid, low dustiness

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 8  
**Contributing exposure scenario controlling worker exposure for**

# SAFETY DATA SHEET



Neopentyl glycol flake  
10470

Version / Revision 4.01

## PROC 19

### Further specification

Assessment tool used: Chesar 2.2

### Product characteristics

Covers percentage substance in the product up to 10 %

Solid, low dustiness

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 1 hour

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 1980 cm<sup>2</sup>

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

Without local exhaust ventilation. provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Wear protective gloves (Efficiency: 80 %).

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 5	EE(inhal): 0.6 ; EE(derm): 8.226
Proc 8a	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 8b	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 10	EE(inhal): 0.18 ; EE(derm): 9.875
Proc 11	EE(inhal): 0.36 ; EE(derm): 7.714
Proc 13	EE(inhal): 0.3 ; EE(derm): 8.226
Proc 14	EE(inhal): 0.6 ; EE(derm): 2.058
Proc 19	EE(inhal): 0.06 ; EE(derm): 3.394

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 5	RCR(inhal): 0.017 ; RCR(derm): 0.823
Proc 8a	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 8b	RCR(inhal): .?1; RCR(derm): .?2
Proc 10	RCR(inhal): 0.01 ; RCR(derm): 0.988
Proc 11	RCR(inhal): 0.01 ; RCR(derm): 0.771
Proc 13	RCR(inhal): 0.01 ; RCR(derm): 0.823
Proc 14	RCR(inhal): 0.017 ; RCR(derm): 0.206
Proc 19	RCR(inhal): 0.01 ; RCR(derm): 0.339

### Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as M(site) [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

### associated uses:

# SAFETY DATA SHEET



**Neopentyl glycol flake**  
**10470**

**Version / Revision** 4.01

---

Should consumer uses be associated with this exposure scenario, please contact OQ for further details  
Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe